

REV	DESCRIPTION OF REVISION	ECN No.	BY	DATE	APPROVED
A	INITIAL RELEASE	—	L. Ma	11/19/11	M. Dong

TECHNICAL DATA

■ Electrical data


Impedance	50 Ω
Frequency range	0~6 GHz
Insulation resistance	$\geq 5 \times 10^3$ M Ω
Withstanding voltage	1000 V

■ Mechanical data

Temperature range	-65 °C ~ +165 °C
Durability (matings)	>500


■ Material data

Bodies	Brass, Nickel-plated
Pin Contact	Brass & Copper beryllium alloy, Gold-plated
Coupling Nut	Brass, Nickel-plated
Insulator	PTFE
Gasket	Silicone Rubber



NOTES:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 11/19/11	TITLE: Adapter, Right Angle, N Male to SMA Female	 www.cmppter.com			
ENGINEER: J. Zhu 11/19/11					
APPROVED: M. Dong 11/19/11		 DIMENSIONS IN MILLIMETERS (mm)			
TOLERANCE UNLESS OTHERWISE SPECIFIED	PART No.: AR-NM-SMAF-232	SIZE: A4	SCALE: 2:1	SHEET: 1/1	REV: A
X ± 0.50 [.019"] .X ± 0.20 [.008"] .XX ± 0.10 [.004"] ANGLES $\pm 1^\circ$					