

REV	DESCRIPTION OF REVISION	ECN No.	BY	DATE	APPROVED
A	INITIAL RELEASE	—	H. Xiao	03/03/11	M. Dong

TECHNICAL DATA

■ Electrical data

Impedance	50 Ω
Frequency range	0~27 GHz
VSWR	1.10:1 (0~18GHz) 1.15:1 (18GHz~27GHz)
Contact resistance	
-centre contact	≤3mΩ
-outer contact	≤2mΩ
Insulation resistance	≥5000MΩ

■ Mechanical data


Temperature range	-55 °C ~ +165 °C
Durability (matings)	>500

■ Material data

Body	Stainless Steel (SU303), Passivated
Pin Contact	Beryllium Copper Alloy, Gold-plated
Insulator	PEI, PTFE

■ Interface Standards

SMA	MIL-STD-348A
-----	--------------



Part Number	Figure
60-02-9F6-101A	Fig. 1
60-02-9F6-101B	Fig. 2




Fig. 1





Fig. 2

NOTES:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H. Xiao 03/03/11	TITLE: SMA Straight Female, Metal Through the Wall, 4 Hole Flange	 www.cmpter.com			
ENGINEER: YF. Zhu 03/03/11		 DIMENSIONS IN MILLIMETERS (mm)			
APPROVED: M. Dong 03/03/11					
TOLERANCE UNLESS OTHERWISE SPECIFIED					
X ±0.50 [.019"] .X ±0.20 [.008"] .XX ±0.10 [.004"] ANGLES ±1°		PART No.: 60-02-9F6-101	SIZE: A4	SCALE: 4:1	SHEET: 1/1