

TECHNICAL DATA

Electrical

Impedance	50 Ω
Frequency range	0~6 GHz
VSWR	1.25:1
Average Power	2W

Mechanical & Environmental

Durability (matings)	>500
Temperature range	-55 °C ~ +125 °C
RoHS Compliant	Yes



Material & Finish

Body	Brass, Nickel-plated
Pin Contact	Brass, Gold-plated
Coupling Nut	Brass, Nickel-plated
Insulator	PTFE
Gasket	Silicone Rubber

Interface Standards

TNC	MIL-STD-348A
-----	--------------

REVISIONS				
REV	DESCRIPTION OF REVISION	ECN No.	DATE	APPROVED
A	INITIAL RELEASE	—	09/11/2010	M. Dong



NOTES:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS
ARE IN MILLIMETERS [INCHES].
UNLESS OTHERWISE SPECIFIED DIMENSIONAL
TOLERANCES ARE:

.XX	±0.13 [.005"]
.X	±0.20 [.008"]
X	±0.50 [.019"]

ANGULAR TOLERANCES ARE: ALL ±1°

DO NOT SCALE DRAWING

PROJECTION:

DRAWN:	L. Ma	09/11/2010
CHECKED:	J. Zhu	09/11/2010
APPROVED:	M. Dong	09/11/2010

TITLE:

Termination, TNC Male,
2 Watts, DC to 6GHz

CMPter®

Cmptter Electronics Co., Ltd. www.cmptter.com

PART No.:
T-TNCM-026

SIZE: A4	SCALE: 2.5:1	SHEET: 1/1	REV: A
-------------	-----------------	---------------	-----------