

TECHNICAL DATA

Electrical

Impedance 50 Ω
Frequency range 0~6 GHz
Withstanding voltage 250 V
Insulation resistance ≥1000MΩ

Mechanical & Environmental

Durability (matings) >500
Temperature range -55 °C ~ +155 °C
RoHS Compliant Yes




Material & Finish

Body Brass, Tri-Metal -plated
Pin Contact Beryllium Copper Alloy, Gold-plated
Fastening Nut Brass, Tri-Metal -plated
Insulator PTFE

Interface Standards

TNC MIL-STD-348A
MCX MIL-STD-348A

REVISIONS				
REV	DESCRIPTION OF REVISION	ECN No.	DATE	APPROVED
A	INITIAL RELEASE		02/14/2019	M. Dong



Recommended Mounting Hole

- NOTES:
- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
 - UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS [INCHES]. UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE: .XX ±0.13 [.005"] X ±0.20 [.008"] X ±0.50 [.019"] ANGULAR TOLERANCES ARE: ALL= ±1°	
DO NOT SCALE DRAWING	
PROJECTION:	

DRAWN:	L. Ma	02/14/2019
CHECKED:	J. Zhu	02/14/2019
APPROVED:	M. Dong	02/14/2019

TITLE:
Adapter, TNC Bulkhead
Female to MCX Female

 Cmpter Electronics Co., Ltd. www.cmpter.com			
PART No.: A-TNCF-MCXF-356			
SIZE: A4	SCALE: 2.5:1	SHEET: 1/1	REV: A