



REVISIONS				
REV	DESCRIPTION OF REVISION	ECN No.	DATE	APPROVED
A	INITIAL RELEASE	—	05/28/2020	M. Dong

Impedance	50 Ω
Frequency range	0~3 GHz
Working voltage	250 Vrms
Insulation resistance	≥5000MΩ

Durability (matings)	>500
Temperature range	-55 °C ~ +165 °C
RoHS Compliant	Yes

Body	Brass, Nickel-plated
Pin Contact	Phosphor Bronze, Gold-plated
Washer	Phosphor Bronze, Nickel-plated
Insulator	PTFE
Gasket	Silicone Rubber

N IEC-60169



NOTES:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS
ARE IN MILLIMETERS [INCHES].
UNLESS OTHERWISE SPECIFIED DIMENSIONAL
TOLERANCES ARE:

.XX	±0.13 [.005"]
.X	±0.20 [.008"]
X	±0.50 [.019"]

ANGULAR TOLERANCES ARE: ALL=±1°

DO NOT SCALE DRAWING

PROJECTION:



DRAWN:	L. Ma	05/28/2020
CHECKED:	J. Zhu	05/28/2020
APPROVED:	M. Dong	05/28/2020

TITLE:
N Straight Bulkhead Waterproof
Female Crimp for RG178/1.37mm
Cable

CMP[®]TER
Cmpter Electronics Co., Ltd. www.cmpter.com

PART No.:

50-02-1C23-269

SIZE: A4	SCALE: 2:1	SHEET: 1/1	REV: A
-------------	---------------	---------------	-----------