

REVISIONS				
REV	DESCRIPTION OF REVISION	ECN No.	DATE	APPROVED
A	INITIAL RELEASE	—	04/16/2007	M. Dong

TECHNICAL DATA

Electrical

Impedance	50 Ω
Frequency range	0~3 GHz
Insulation resistance	$\geq 5 \times 10^3$ M Ω
Withstanding voltage	2500 V

Mechanical & Environmental



Durability (matings)	>500
Temperature range	-55 °C ~ +165 °C
RoHS Compliant	Yes

Material & Finish

Body	Brass, Nickel-plated
Pin Contact	Brass, Gold-plated
Coupling Nut	Brass, Nickel-plated
Crimp Ferrule	Copper, Nickel-plated
Insulator	PTFE
Gasket	Silicone Rubber


Interface Standards

N	IEC-60169
---	-----------



Cable Stripping Dimensions

1. CRIMP FERRULE
HEX. CRIMP TOOL SIZE : 10.9 [.429]



NOTES:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS (INCHES).
UNLESS OTHERWISE SPECIFIED DIMENSIONAL TOLERANCES ARE:

XX	± 0.13 [.005"]
X	± 0.20 [.008"]
X	± 0.50 [.019"]

ANGULAR TOLERANCES ARE: ALL $\pm 1^\circ$

DO NOT SCALE DRAWING

PROJECTION:



DRAWN:	L. Ma	04/16/2007
CHECKED:	J. Zhu	04/16/2007
APPROVED:	M. Dong	04/16/2007

TITLE:

N Right Angle Male crimp for LMR400 Cable

CMPPTER®

Cmppter Electronics Co., Ltd. www.cmppter.com

PART No.:

50-13-1M01-019

SIZE: A4	SCALE: 2:1	SHEET: 1/1	REV: A
----------	------------	------------	--------