

REV	DESCRIPTION OF REVISION	ECN No.	BY	DATE	APPROVED
A	INITIAL RELEASE	—	H. Xiao	11/02/10	11/02/10

TECHNICAL DATA

■ Electrical data

Impedance	50 Ω
Frequency range	0~40 GHz
VSWR	1.20:1
Contact resistance	
-centre contact	$\leq 5\text{m}\Omega$
-outer contact	$\leq 2.5\text{m}\Omega$
Insulation resistance	$\geq 1000\text{M}\Omega$

■ Mechanical data


Temperature range	-55 °C ~ +165 °C
Durability (matings)	>500

■ Material data


Body	Stainless Steel (SU303), Passivated
Pin Contact	Beryllium Copper Alloy, Gold-plated
Insulator	PEI, PTFE

■ Interface Standards

SSMA	MIL-STD-348A
------	--------------




Part Number	Figure
D60-02-9E5-008A	Fig. 1
D60-02-9E5-008B	Fig. 2



NOTES:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H. Xiao 11/02/10	TITLE: SSMA Straight Female, 2 Hole Flange, Metal Through the Wall	 www.cmpter.com			
ENGINEER: YF. Zhu 11/02/10					
APPROVED: M. Dong 11/02/10		 DIMENSIONS IN MILLIMETERS (mm)			
TOLERANCE UNLESS OTHERWISE SPECIFIED	PART No.: D60-02-9E5-008	SIZE: A4	SCALE: 4:1	SHEET: 1/1	REV: A